

I catch DVR-411ZS-J H.264 D1 錄影機



- 4 通道 H.264 D1 DVR
- 4 聲道輸入, 2 組輸出
- 支援 VGA, BNC 螢幕輸出
- 支援三模影音串流(Triple Streaming)
- 支援中央管理系統 CMS (Central Management System)。
- 支援 Mac 系統
- 支援觸控螢幕
- 支援 3G 行動監控
- HDMI 輸出(選購)

Model		411ZS-J
Camera Input		4CH
Video	HDMI	1 (Option) (Video Output [1280x1024] + Audio Output)
	Input	4
	Output	2 BNC (1 BNC for Main monitor, 1 BNC for Co-monitor) , 1 VGA (max. 1280X1024)
Audio	Input	4 RCA
	Output	2 RCA
System	Operating System	Embedded Linux OS
	SATA Devices	Supports 1 SATA Device (HDDx1)
	External HDD	N/A
	Sensor In (NO, NC)	Sensor-in x 4
	Relay out	Relay-out x 1
	Serial Interface	RS-485
	USB	2 x USB2.0
	Dimension (mm)	W: 280(w)x51(h)x203(d)
	Weight (w/o HDD/DVD;RW)	1.00KG
	Power Supply	Input 100~240V, Output 12V 2A
Power Rating	24W	
Display	Speed	120 fps
	Resolution (Pixel)	720 X 480(NTSC), 720 X 576(PAL)
	Split screen	1,4, SEQ.
	Auto Channel Switching	Switching time : 1 ~ 999 sec
	Mode	Zoom (Digital x2~ x8), PIP, Auto SEQ.
Recording	Compression	H.264 Baseline

	Dual Stream Resolution (Pixel)	Main (Recording)	704 X 480, 704 X 240, 352 X 240 (NTSC) / 704 X 576, 704 X 288, 352 X 288 (PAL)
		Sub (Network)	352 x 240 (NTSC), 352 x 288 (PAL)
	Picture quality		5 levels (Highest, High, Normal, Basic, Below Basic)
	Mode		Manual, Motion, Schedule
	Speed	NTSC	D1 120 fps(704 x 480) HD1 120 fps(704 x 240) CIF 120 fps(352 x 240)
		PAL	D1 100 fps(704 x 576) HD1 100 fps(704 x 288) CIF 100 fps(352 x 288)
	Pre-Alarm		10 SEC
	Post-Alarm		1 ~ 60 SEC
Playback	Display		1, 4
	Search mode		Date, time, event, camera
	Zoom		Digital (x2 ~ x8)
	Snapshot		YES
	Speed		Normal, REW & FF (recorded speed x2, x4, x8, x16, x32, x64), Frame to frame, Pause
	Device		Int. HDD
Network	Network Interface		10/100 Ethernet
	Protocol		TCP/IP, SMTP, HTTP, DHCP, PPPoE(ADSL), NTP
	Application		Windows XP/VISTA/7(PC Client system)
	Remote Software		Application Software, IE Browser
	Account		1 Admin + 10 Users
	CMS		Yes
	Mobile		Symbian, Windows Mobile, Blackberry, iPhone, Android phone
	Event Transport		E-mail, FTP
Backup	Interface		USB 2.0 or SATA
	Audio Backup		YES
	Network		YES
	Backup Device (Optional)		Network Backup / USB Flash Drive / USB DVD;RW
Alarm	Motion Detection		Detected Frames: Channel
			Sensitivity : 10 levels for each channel

		Area : Programmable individually
	Search (Event Criterion)	YES
	Event Log	Up to the 10000 events (Sensor, Motion, video Loss, power on, remote login, logout, HDD error, HDD full)
OSD & DVR Control	GUI	16-bit True Color
	Multi-Language	English, Traditional Chinese, Others
	Camera Title	Multi-Language
	USB Mouse	YES
	Touch Panel	Touch Panel LCD Monitor (USB Interface, EETI Chipset Only)
	Remote Controller	IR Remote Control (Max. 1 Device)
	System Upgrade	via USB / Network
	Hard Key	Front Panel
	Pan / Tilt / Zoom Control	Control From RS-485 Interface (Pelco P, Pelco D, Samsung, LG, LiLin)